



安徽富信半导体科技有限公司

ANHUI FOSAN SEMICONDUCTOR TECHNOLOGY CO., LTD.

M28S


SOT-23 Bipolar Transistor 双极型三极管

SOT-23

■ Features 特点

NPN General Purpose 通用

- 1. BASE
- 2. EMITTER
- 3. COLLECTOR



■ Absolute Maximum Ratings 最大额定值

Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
Collector-Base Voltage 集电极基极电压	V_{CBO}	40	V
Collector-Emitter Voltage 集电极发射极电压	V_{CEO}	20	V
Emitter-Base Voltage 发射极基极电压	V_{EBO}	6	V
Collector Current 集电极电流	I_C	1000	mA
Power dissipation 耗散功率	$P_C(T_a=25^{\circ}C)$	300	mW
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	420	$^{\circ}C/W$
Junction and Storage Temperature 结温和储藏温度	T_J, T_{stg}	-55to+150 $^{\circ}C$	

■ Device Marking 产品打标

M28S=28S









■Electrical Characteristics 电特性


(TA=25°C unless otherwise noted 如无特殊说明, 温度为 25°C)

Characteristic 特性参数	Symbol 符号	Min 最小值	Type 典型值	Max 最大值	Unit 单位
Collector-Base Breakdown Voltage 集电极基极击穿电压(I _C = 100μA, I _E =0)	BV _{CBO}	40	—	—	V
Collector-Emitter Breakdown Voltage 集电极发射极击穿电压(I _C = 1mA, I _B =0)	BV _{CEO}	20	—	—	V
Emitter-Base Breakdown Voltage 发射极基极击穿电压(I _E = 100μA, I _C =0)	BV _{EBO}	6	—	—	V
Collector-Base Leakage Current 集电极基极漏电流(V _{CB} =40V, I _E =0)	I _{CBO}	—	—	0.1	μA
Collector-Emitter Leakage Current 集电极发射极漏电流(V _{CE} =20V, I _B =0)	I _{CEO}	—	—	5	μA
Emitter-Base Leakage Current 发射极基极漏电流(V _{EB} =5V, I _C =0)	I _{EBO}	—	—	0.1	μA
DC Current Gain(V _{CE} = 1V, I _C = 100mA) 直流电流增益(V _{CE} = 1V, I _C = 300mA) (V _{CE} = 1V, I _C = 500mA)	H _{FE}	300 300 300	—	1000	
Collector-Emitter Saturation Voltage 集电极发射极饱和压降(I _C = 600mA, I _B =20mA)	V _{CE(sat)}	—	—	0.55	V
Base-Emitter Saturation Voltage 基极发射极饱和压降(I _C = 600mA, I _B = 20mA)	V _{BE(sat)}	—	—	1.2	V
Transition Frequency 特征频率(V _{CE} = 10V, I _C = 50mA)	f _T	—	100	—	MHz
Output Capacitance 输出电容(V _{CB} = 10V, I _E =0, f=1MHz)	C _{ob}	—	10	—	pF

■ Typical Characteristic Curve 典型特性曲线



■Dimension 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.050	0.055
E1	2.250	2.550	0.089	0.100
e	0.950TYP		0.037TYP	
e1	1.800	2.000	0.071	0.079
L	0.550REF		0.022REF	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°