安徽富信半导体科技有限公司

ANHUI FOSAN SEMICONDUCTOR TECHNOLOGY CO. , LTD.

FS4946

SOP-8 60V Dual N Channel Enhancement 双 N 沟道增强型
MOS Field Effect Transistor 场效应管

■Features 特点

Low on-resistance 低导通电阻
$R_{DS(ON)}$=38mΩ(Type)@V_{GS}=10V
$R_{DS(ON)}$=43mΩ(Type)@V_{GS}=4.5V

■Applications 应用

DC/DC Converter 升压转换
Powered Management 电源管理
LCD Display Converter 液晶屏背光驱动
Load Switch 负载开关
Portable Equipment 桌面设备

■Internal Schematic Diagram 内部结构





■Absolute Maximum Ratings 最大额定值

Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
Drain-Source Voltage 漏极-源极电压	BV_{DSS}	60	V
Gate- Source Voltage 栅极-源极电压	V_{GS}	±20	V
Drain Current (continuous)漏极电流-连续	I_D（at T_A = 25°C）	5.3	A
Drain Current (pulsed)漏极电流-脉冲	I_{DM}	30	A
Total Device Dissipation 总耗散功率	P_D(at T_A = 25°C)	2400	mW
Thermal Resistance Junction-Ambient 热阻	$R_{\Theta JA}$	52	℃/W
Junction/Storage Temperature 结温/储存温度	T_J,T_{stg}	-55~150	℃

■Electrical Characteristics 电特性

(T_A=25℃ unless otherwise noted 如无特殊说明，温度为 25℃)

Characteristic 特性参数	Symbol 符号	Min 最小值	Typ 典型值	Max 最大值	Unit 单位
Drain-Source Breakdown Voltage 漏极-源极击穿电压(I_D =250uA,V_{GS}=0V)	BV_{DSS}	60	—	—	V
Gate Threshold Voltage 栅极开启电压(I_D =250uA,V_{GS}= V_{DS})	$V_{GS(th)}$	1	2.4	3	V
Zero Gate Voltage Drain Current 零栅压漏极电流(V_{GS}=0V, V_{DS}= 48V)	I_{DSS}	—	—	1	uA
Gate Body Leakage 栅极漏电流(V_{GS}=±20V, V_{DS}=0V)	I_{GSS}	—	—	±100	nA
Static Drain-Source On-State Resistance 静态漏源导通电阻(I_D=5.3A,V_{GS}=10V) (I_D=3A,V_{GS}=4.5V)	$R_{DS(ON)}$	—	38 43	45 58	mΩ
Diode Forward Voltage Drop 内附二极管正向压降(I_{SD}=1A,V_{GS}=0V)	V_{SD}	—	0.8	1.2	V
Input Capacitance 输入电容 (V_{GS}=0V, V_{DS}=30V,f=1MHz)	C_{ISS}	—	840	—	pF
Common Source Output Capacitance 共源输出电容(V_{GS}=0V, V_{DS}=30V,f=1MHz)	C_{OSS}	—	71	—	pF
Reverse Transfer Capacitance 反馈电容 (V_{GS}=0V, V_{DS}=30V,f=1MHz)	C_{RSS}	—	44	—	pF
Total Gate Charge 栅极电荷密度 (V_{DS}=30V, I_D=5A, V_{GS}=10V)	Q_g	—	9	—	nC
Gate Source Charge 栅源电荷密度 (V_{DS}=30V, I_D=5A, V_{GS}=10V)	Q_{gs}	—	3	—	nC
Gate Drain Charge 栅漏电荷密度 (V_{DS}=30V, I_D=5A, V_{GS}=10V)	Q_{gd}	—	4	—	nC
Turn-ON Delay Time 开启延迟时间 (V_{DS}=30V I_D=1A, R_{GEN}=6Ω,V_{GS}=10V)	$t_{d(on)}$	—	20	—	ns
Turn-ON Rise Time 开启上升时间 (V_{DS}=30V I_D=1A, R_{GEN}=6Ω,V_{GS}=10V)	t_r	—	120	—	ns
Turn-OFF Delay Time 关断延迟时间 (V_{DS}=30V I_D=1A, R_{GEN}=6Ω,V_{GS}=10V)	$t_{d(off)}$	—	20	—	ns
Turn-OFF Fall Time 关断下降时间 (V_{DS}=30V I_D=1A, R_{GEN}=6Ω,V_{GS}=10V)	t_f	—	30	—	ns

■Typical Characteristic Curve 典型特性曲线



Figure 1: Output Characteristics



Figure 2: Transfer Characteristics



Figure 3: Threshold Voltage vs. Temperature



Figure 4: On-Resistance vs. Temperature



Figure 5: Capacitance Characteristics



Figure 6: Gate-Charge Characteristics

■Typical Characteristic Curve 典型特性曲线



Figure 7: Diode Characteristics



Figure 8: Safe Operating Area



Figure 9: Switching Test Circuit



Figure 10: Switching Waveform



Figure 11: Transient Thermal Response Curve

■**Dimension** 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.350	1.750	0.053	0.069
A1	0.100	0.250	0.004	0.010
A2	1.350	1.550	0.053	0.061
b	0.330	0.510	0.013	0.020
c	0.170	0.250	0.006	0.010
D	4.700	5.100	0.185	0.200
E	3.800	4.000	0.150	0.157
E1	5.800	6.200	0.228	0.244
e	1.270(BSC)		0.050(BSC)	
L	0.400	1.270	0.016	0.050
θ	0°	8°	0°	8°