

**SOD-323 Schottky Barrier Diode 肖特基势垒二极管****■ Internal Configuration& Device Marking 内部结构与产品打标**

Type 型号	RB551V-30	
Pin 管脚		
Mark 打标	D	

**■ Absolute Maximum Ratings 最大额定值**





Characteristic 特性参数	Symbol 符号	Rating 额定值	Unit 单位
Peak Reverse Voltage 反向峰值电压	V <sub>RM</sub>	30	V
DC Reverse Voltage 直流反向电压	V <sub>R</sub>	20	
Forward Work Current 正向工作电流	I <sub>O</sub>	500	mA
Peak Forward Surge Current 正向峰值浪涌电流	I <sub>FSM</sub>	2000	mA
Power dissipation 耗散功率	P <sub>D</sub> (Ta=25°C)	200	mW
Thermal Resistance J-A 结到环境热阻	R <sub>θJA</sub>	500	°C/W
Junction and Storage Temperature 结温和储藏温度	T <sub>J</sub> , T <sub>stg</sub>	-55 to +125°C	

**■ Electrical Characteristics 电特性**


(TA=25°C unless otherwise noted 如无特殊说明, 温度为 25°C)

Characteristic 特性参数	Symbol 符号	Min 最小值	Max 最大值	Unit 单位
Reverse Breakdown Voltage 反向击穿电压(IR=0.1mA)	V <sub>(BR)</sub>	30	—	V
Reverse Leakage Current 反向漏电流(VR=20V)	I <sub>R</sub>	—	100	μA
Forward Voltage(I <sub>F</sub> =100mA) 正向电压(I <sub>F</sub> =500mA)	V <sub>F</sub>		0.36 0.47	V
Diode Capacitance 二极管电容(VR=1V, f=1MHz)	C <sub>D</sub>	—	100	pF

■Typical Characteristic Curve 典型特性曲线



■Dimension 外形封装尺寸



COMMON DIMENSIONS (UNITS OF MEASURE IS mm)			
	MIN	NORMAL	MAX
A	1.600	1.700	1.800
B	1.200	1.300	1.400
C	0.750	0.850	0.950
C1	0.450	0.500	0.550
D	2.450	2.600	2.750
L	0.200	0.300	0.400
b	0.200	0.300	0.400
h	0.010	0.050	0.100
θ1	9° TYPE		
θ2	9° TYPE		
θ3	0° ~ 8°		