


TO-277B Schottky Barrier Rectifier Diode 肖特基势垒整流二极管**■Features 特点**

Low forward voltage drop 低正向压降
 High current capability 高电流能力
 Surface mount device 表面贴装器件
 Case 封装:TO-277B

**■Maximum Rating 最大额定值**

(TA=25°C unless otherwise noted 如无特殊说明, 温度为 25°C)

Characteristic 特性参数	Symbol 符号	SS 2040	SS 2045	SS 2060	SS 2080	SS 20100	SS 20150	SS 20200	Unit 单位
Peak Reverse Voltage 反向峰值电压	V _{RRM}	40	45	60	80	100	150	200	V
DC Reverse Voltage 直流反向电压	V _R	40	45	60	80	100	150	200	V
RMS Reverse Voltage 反向电压均方根值	V _{R(RMS)}	28	32	42	56	70	105	140	V
Forward Rectified Current 正向整流电流	I _F				20				A
Peak Surge Current 峰值浪涌电流	I _{FSM}				250				A
Thermal Resistance J-A 结到环境热阻	R _{θJA}				60				°C/W
Junction Temperature 结温	T _J				150				°C
Storage Temperature 储藏温度	T _{stg}				-55to+150°C				°C

■Electrical Characteristics 电特性

(TA=25°C unless otherwise noted 如无特殊说明, 温度为 25°C)

Characteristic 特性参数	Symbol 符号	SS2040- SS2045	SS2060	SS2080- SS20100	SS20150- SS20200	Unit 单位	Condition 条件
Forward Voltage 正向电压	V _F	0.55	0.70	0.85	0.92	V	I _F =20A
Reverse Current 反向电流	I _R (25°C) (125°C)	0.1 50		0.01 20		mA	V _R =V _{RRM}
Diode Capacitance 二极管电容	C _D		800			pF	V _R =4V,f=1MHz

■Typical Characteristic Curve 典型特性曲线

FIG. 1- DERATING CURVE OUTPUT RECTIFIED CURRENT




FIG. 2-MAXIMUM NON-REPETITIVE PEAK FORWARD SURGE CURRENT PERLEG




FIG. 3-TYPICAL FORWARD VOLTAGE CHARACTERISTICS








FIG. 4-TYPICAL REVERSE LEAKAGE CHARACTERISTICS



■Dimension 外形封装尺寸 Dimensions in inches and (millimeters)



Suggested Soldering Temperature Profile 焊接**Package Information 包装****Carrier Dimension(mm)**

A0	B0	K0	D0	E	F
4.40	6.90	1.30	1.55	1.75	7.50
P0	P1	P2	T	W	Tolerance
4.0	8.0	2.0	0.25	12	0.1

Package Specifications

Package	Reel Size	Reel DIA. (mm)	Q'TY/Reel (Kpcs)	Box Size (mm)	QTY/Box (Kpcs)	Carton Size (mm)	Q'TY/Carton (Kpcs)
TO-277B	13'	330	5.0	340	10.0	360*360*360	80