

SOD-323 ESD 静电保护二极管

■Features 特点

Bidirectional 双向

Ultra-low Capacitance 超低电容

■Applications 应用


I/O Interfaces 输入输出接口

Industrial and Serve Robots 工业和服务机器人

Laptops and Desktops 便携和台式电脑

TV and Monitors 电视和监视器

Wearables 可穿戴电子产品



■Device Marking 产品打标

$V_{RWM}(V)$	3	5
Marking	CC	AC/3B/LC

■Absolute Maximum Ratings 最大额定值


Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
ESD (IEC61000-4-2 contact discharge) @25°C接触放电	V_{ESD}	± 25	KV
ESD (IEC61000-4-2 air discharge) @25°C空气放电	V_{ESD}	± 25	KV
Peak Pulse Power @25°C峰值脉冲功率	P_{PK}	200	W
Lead Temperature 管脚温度	T_L	260	°C
Lead Solder Time 管脚焊接时间	T_L	10	S
Operating Temperature 工作温度	T_{op}	-40~85	°C
Junction Temperature 结温	T_J	-55~125	°C
Storage Temperature 储存温度	T_{stg}	-55~150	°C

■ Electrical Characteristics 电特性


($T_A=25^{\circ}\text{C}$ unless otherwise noted 如无特殊说明, 温度为 25°C)

Part No.型号	V_{RWM} (V)	$V_{\text{R(BR)}}$ (V)	$V_{\text{C}}(\text{V})@I_{\text{T}}=1\text{A}$	$I_{\text{PP}}(\text{A})$	$V_{\text{C}}(\text{V})@I_{\text{T}}=I_{\text{PP}}$	$I_{\text{R}}(\mu\text{A})$	$C_{\text{J}}(\text{pF})$
FSLC3D3V1BB	3.0	3.8	7.0	10.0	16.0	1.0	0.8
FSLC3D5V1BB	5.0	6.5	8.0	10.0	16.0	1.0	0.8


V_{RWM}	Reverse Working Voltage 反向工作电压
$V_{\text{R(BR)}}$	Reverse Breakdown Voltage 反向击穿电压@ $I_{\text{T}}=1\text{mA}$
I_{T}	Test Current 测试电流
I_{R}	Reverse Leakage Current 反向漏电流@ V_{RWM}
V_{C}	Clamping Voltage 钳位电压
I_{PP}	Reverse Peak Pulse Current 浪涌电流
C_{J}	Junction Capacitance 结电容 $V_{\text{IO}}=0\text{V}$, $V_{\text{P-P}}=30\text{mV}$, $f=1\text{MHz}$




■ Typical Characteristic Curve 典型特性曲线




Non-repetitive peak pulse power vs. pulse time



■ Typical Application 典型应用



■ Dimension 外形封装尺寸



Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min.	Max.	Min.	Max.
A		1.000		0.039
A1	0.000	0.100	0.000	0.004
A2	0.800	0.900	0.031	0.035
b	0.250	0.350	0.010	0.014
C	0.080	0.150	0.003	0.006
D	1.200	1.400	0.047	0.055
E	1.600	1.800	0.063	0.071
E1	2.550	2.750	0.100	0.108
L	0.475REF		0.019REF	
L1	0.250	0.400	0.010	0.016
θ	0°	8°	0°	8°