


SOT-323 Bipolar Transistor 双极型三极管

■ Features 特点

NPN General Purpose 通用



■ Absolute Maximum Ratings 最大额定值

Characteristic 特性参数	Symbol 符号	BC846 AW/BW	BC847 AW/BW/CW	BC848 AW/BW/CW	Unit 单位
Collector-Base Voltage 集电极基极电压	V_{CBO}	80	50	30	V
Collector-Emitter Voltage 集电极发射极电压	V_{CEO}	65	45	30	V
Emitter-Base Voltage 发射极基极电压	V_{EBO}	6	6	5	V
Collector Current 集电极电流	I_C	100			mA
Power dissipation 耗散功率	$P_C(T_a=25^{\circ}\text{C})$	150			mW
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	833			$^{\circ}\text{C/W}$
Junction and Storage Temperature 结温和储藏温度	T_J, T_{stg}	-55to+150 $^{\circ}\text{C}$			

■ Device Marking 产品打标


H_{FE}		110-220(AW)	200-450(BW)	420-800(CW)
Mark	BC846	1A	1B	
	BC847	1E	1F	1G
	BC848	1J	1K	1L

■Electrical Characteristics 电特性


(TA=25℃ unless otherwise noted 如无特殊说明, 温度为 25℃)

Characteristic 特性参数		Symbol 符号	Min 最小值	Type 典型值	Max 最大值	Unit 单位
Collector-Base Breakdown Voltage 集电极基极击穿电压 (IC=10uA, IE=0)	BC846AW/BW	BV _{CBO}	80	—	—	V
	BC847AW/BW/CW		50			
	BC848AW/BW/CW		30			
Collector-Emitter Breakdown Voltage 集电极发射极击穿电压 (IC=10mA, IB=0)	BC846AW/BW	BV _{CEO}	65	—	—	V
	BC847AW/BW/CW		45			
	BC848AW/BW/CW		30			
Emitter-Base Breakdown Voltage 发射极基极击穿电压 (IE=10uA, IC=0)		BV _{EBO}	5	—	—	V
Collector-Base Leakage Current 集电极基极漏电流	BC846AW/BW(V _{CB} =70V,IE=0)	I _{CBO}	—	—	100	nA
	BC847AW/BW/CW(V _{CB} =50V,IE=0)					
	BC848AW/BW/CW(V _{CB} =30V,IE=0)					
Emitter-Base Leakage Current 发射极基极漏电流 (V _{EB} =5V, IC=0)		I _{EBO}	—	—	100	nA
DC Current Gain 直流电流增益 (V _{CE} =5V,IC=2mA)	BC846AW/BC847AW/BC848AW	H _{FE}	110	180	220	
	BC846BW/BC847BW/BC848BW		200	290	450	
	BC847CW/BC848CW		420	520	800	
Collector-Emitter Saturation Voltage 集电极发射极饱和压降 (IC=100mA, IB=5mA)		V _{CE(sat)}	—	—	0.6	V
Base-Emitter Saturation Voltage 基极发射极饱和压降 (IC=100mA, IB=5mA)		V _{BE(sat)}	—	—	1.1	V
Transition Frequency 特征频率 (V _{CE} =5V, IC=10mA)		f _T	100	—	—	MHz
Output Capacitance 输出电容 (V _{CB} =10V, IE=0, f=1MHz)		C _{ob}	—	4.5	—	pF

■ Typical Characteristic Curve 典型特性曲线



■Dimension 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	0.900	1.100	0.035	0.043
A1	0.000	0.100	0.000	0.004
A2	0.900	1.000	0.035	0.039
b	0.200	0.400	0.008	0.016
c	0.080	0.150	0.003	0.006
D	2.000	2.200	0.079	0.087
E	1.150	1.350	0.045	0.053
E1	2.150	2.450	0.085	0.096
e	0.650 TYP		0.026 TYP	
e1	1.200	1.400	0.047	0.055
L	0.525 REF		0.021 REF	
L1	0.260	0.460	0.010	0.018
θ	0°	8°	0°	8°