


SOT-89-3L Bipolar Transistor 双极型三极管

■Features 特点

NPN Switching 开关



■Absolute Maximum Ratings 最大额定值

Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
Collector-Base Voltage 集电极基极电压	V_{CBO}	60	V
Collector-Emitter Voltage 集电极发射极电压	V_{CEO}	40	V
Emitter-Base Voltage 发射极基极电压	V_{EBO}	6	V
Collector Current 集电极电流	I_C	600	mA
Power dissipation 耗散功率	$P_C(T_a=25^{\circ}\text{C})$	500	mW
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	250	$^{\circ}\text{C}/\text{W}$
Junction and Storage Temperature 结温和储藏温度	T_J, T_{stg}	-55to+150 $^{\circ}\text{C}$	

■Device Marking 产品打标


PXT4401=2X

■Electrical Characteristics 电特性


(TA=25℃ unless otherwise noted 如无特殊说明, 温度为 25℃)

Characteristic 特性参数	Symbol 符号	Min 最小值	Type 典型值	Max 最大值	Unit 单位
Collector-Base Breakdown Voltage 集电极基极击穿电压(IC=10uA, IE=0)	BV _{CBO}	60	—	—	V
Collector-Emitter Breakdown Voltage 集电极发射极击穿电压(IC=1mA, IB=0)	BV _{CEO}	40	—	—	V
Emitter-Base Breakdown Voltage 发射极基极击穿电压(IE=10uA, IC=0)	BV _{EBO}	6	—	—	V
Collector-Base Leakage Current 集电极基极漏电流(V _{CB} =50V, IE=0)	I _{CBO}	—	—	100	nA
Collector-Emitter Leakage Current 集电极发射极漏电流(V _{CE} =35V, V _{BE} =-3V)	I _{CEX}	—	—	100	nA
Emitter-Base Leakage Current 发射极基极漏电流(V _{EB} =5V, IC=0)	I _{EBO}	—	—	100	nA
DC Current Gain(V _{CE} =1V, IC=150mA) 直流电流增益(V _{CE} =1V, IC=0.1mA) (V _{CE} =1V, IC=500mA)	H _{FE}	100 40 40	—	300	
Collector-Emitter Saturation Voltage 集电极发射极饱和压降(IC=500mA, IB=50mA) (IC=150mA, IB=15mA)	V _{CE(sat)}	—	—	1 0.3	V
Base-Emitter Saturation Voltage 基极发射极饱和压降(IC=500mA, IB=50mA) (IC=150mA, IB=15mA)	V _{BE(sat)}	—	—	2 1.2	V
Transition Frequency 特征频率(V _{CE} =20V, IC=20mA)	f _T	300	—	—	MHz
Delay Time 延迟时间 (V _{CC} =30V, V _{BE} =-0.5V, IC=150mA, IB1=15mA)	t _d	—	—	10	ns
Rise Time 上升时间 (V _{CC} =30V, V _{BE} =-0.5V, IC=150mA, IB1=15mA)	t _r	—	—	25	ns
Storage Time 贮存时间 (V _{CC} =30V, IC=150mA, IB1=IB2=15mA)	t _s	—	—	225	ns
Fall Time 下降时间 (V _{CC} =30V, IC=150mA, IB1=IB2=15mA)	t _f	—	—	60	ns

■ Typical Characteristic Curve 典型特性曲线



■Dimension 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.40	1.60	0.055	0.063
B	0.40	0.56	0.016	0.022
B1	0.35	0.48	0.014	0.019
C	0.35	0.44	0.014	0.017
D	4.40	4.60	0.173	0.181
D1	1.35	1.83	0.053	0.072
e	1.45	1.55	0.057	0.061
e1	2.95	3.05	0.116	0.120
E	2.29	2.60	0.090	0.102
H	3.75	4.25	0.148	0.167
L	0.80	1.20	0.031	0.047