



SOT-89-3L Bipolar Transistor 双极型三极管

■ Features 特点

NPN Low Saturation Voltage 低饱和压降

■ Absolute Maximum Ratings 最大额定值



Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
Collector-Base Voltage 集电极基极电压	V_{CB0}	100	V
Collector-Emitter Voltage 集电极发射极电压	V_{CEO}	60	V
Emitter-Base Voltage 发射极基极电压	V_{EBO}	6	V
Collector Current 集电极电流	I_C	3000	mA
Power dissipation 耗散功率	$P_C(T_a=25^{\circ}\text{C})$	500	mW
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	250	$^{\circ}\text{C}/\text{W}$
Junction and Storage Temperature 结温和储藏温度	T_J, T_{stg}	-55to+150 $^{\circ}\text{C}$	

■ Device Marking 产品打标







H_{FE}	82-180(P)	120-270(Q)	180-390(R)
Mark	DTAP	DTAQ	DTAR

■Electrical Characteristics 电特性


(TA=25℃ unless otherwise noted 如无特殊说明, 温度为 25℃)

Characteristic 特性参数	Symbol 符号	Min 最小值	Type 典型值	Max 最大值	Unit 单位
Collector-Base Breakdown Voltage 集电极基极击穿电压 (IC= 100μA, IE=0)	BV _{CBO}	100	—	—	V
Collector-Emitter Breakdown Voltage 集电极发射极击穿电压 (IC= 1mA, IB=0)	BV _{CEO}	60	—	—	V
Emitter-Base Breakdown Voltage 发射极基极击穿电压 (IE= 100μA, IC=0)	BV _{EBO}	6	—	—	V
Collector-Base Leakage Current 集电极基极漏电流 (VCB= 80V, IE=0)	IC _{BO}	—	—	100	nA
Emitter-Base Leakage Current 发射极基极漏电流 (VEB= 5V, IC=0)	IE _{BO}	—	—	100	nA
DC Current Gain(VCE= 2V, IC= 500mA) 直流电流增益(VCE= 2V, IC= 2000mA)	H _{FE}	82 50	—	390	
Collector-Emitter Saturation Voltage 集电极发射极饱和压降 (IC= 2000mA, IB= 200mA)	V _{CE(sat)}	—	—	600	mV
Base-Emitter Saturation Voltage 基极发射极饱和压降 (IC= 2000mA, IB= 200mA)	V _{BE(sat)}	—	—	1200	mV
Transition Frequency 特征频率 (VCE= 2V, IC= 500mA)	f _T	—	210	—	MHz
Output Capacitance 输出电容 (VCB= 10V, IE=0, f=1MHz)	C _{ob}	—	21	—	pF

■ Typical Characteristic Curve 典型特性曲线



■Dimension 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.40	1.60	0.055	0.063
B	0.40	0.56	0.016	0.022
B1	0.35	0.48	0.014	0.019
C	0.35	0.44	0.014	0.017
D	4.40	4.60	0.173	0.181
D1	1.35	1.83	0.053	0.072
e	1.45	1.55	0.057	0.061
e1	2.95	3.05	0.116	0.120
E	2.29	2.60	0.090	0.102
H	3.75	4.25	0.148	0.167
L	0.80	1.20	0.031	0.047