


SOT-89-3L Bipolar Transistor 双极型三极管

■ Features 特点

NPN High Voltage 高压

■ Absolute Maximum Ratings 最大额定值



Characteristic 特性参数	Symbol 符号	Rat 额定值		Unit 单位
		BST39	BST40	
Collector-Base Voltage 集电极基极电压	V_{CBO}	400	300	V
Collector-Emitter Voltage 集电极发射极电压	V_{CEO}	350	250	V
Emitter-Base Voltage 发射极基极电压	V_{EBO}	5		V
Collector Current 集电极电流	I_C	100		mA
Power dissipation 耗散功率	$P_C(T_a=25^{\circ}\text{C})$	500		mW
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	250		$^{\circ}\text{C}/\text{W}$
Junction and Storage Temperature 结温和储藏温度	T_J, T_{stg}	-55to+150 $^{\circ}\text{C}$		

■ Device Marking 产品打标


BST39=AT1
BST40=AT2

■Electrical Characteristics 电特性


(TA=25℃ unless otherwise noted 如无特殊说明, 温度为 25℃)

Characteristic 特性参数		Symbol 符号	Min 最小值	Type 典型值	Max 最大值	Unit 单位
Collector-Base Breakdown Voltage 集电极基极击穿电压(IC=100μA, IE=0)	BST39 BST40	BV _{CBO}	400 300	—	—	V
Collector-Emitter Breakdown Voltage 集电极发射极击穿电压(IC=1mA, IB=0)	BST39 BST40	BV _{CEO}	350 250	—	—	V
Emitter-Base Breakdown Voltage 发射极基极击穿电压(IE=100μA, IC=0)		BV _{EBO}	5	—	—	V
Collector-Base Leakage Current 集电极基极漏电流(V _{CB} =300V, IE=0)		I _{CBO}	—	—	20	nA
Emitter-Base Leakage Current 发射极基极漏电流(V _{EB} = 5V, IC=0)		I _{EBO}	—	—	100	nA
DC Current Gain 直流电流增益(V _{CE} =10V, IC=20mA)		H _{FE}	40	—	—	
Collector-Emitter Saturation Voltage 集电极发射极饱和压降(IC=50mA, IB= 4mA)		V _{CE(sat)}	—	—	0.5	V
Base-Emitter Saturation Voltage 基极发射极饱和压降(IC=50mA, IB=4mA)		V _{BE(sat)}	—	—	1.2	V
Base-Emitter On Voltage 基极发射极导通电压(V _{CE} = 5V, IC= 30mA)		V _{BE(on)}	—	—	1.2	V
Transition Frequency 特征频率(V _{CE} = 10V, IC= 10mA)		f _T	—	70	—	MHz
Output Capacitance 输出电容(V _{CB} = 10V, IE=0, f=1MHz)		C _{ob}	—	2	—	pF

■ Typical Characteristic Curve 典型特性曲线



■Dimension 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.40	1.60	0.055	0.063
B	0.40	0.56	0.016	0.022
B1	0.35	0.48	0.014	0.019
C	0.35	0.44	0.014	0.017
D	4.40	4.60	0.173	0.181
D1	1.35	1.83	0.053	0.072
e	1.45	1.55	0.057	0.061
e1	2.95	3.05	0.116	0.120
E	2.29	2.60	0.090	0.102
H	3.75	4.25	0.148	0.167
L	0.80	1.20	0.031	0.047