

TO-92 Bipolar Transistor 双极型三极管

■ Features 特点

NPN General Purpose 通用


■ Absolute Maximum Ratings 最大额定值

TO-92

1.EMITTER

2.COLLECTOR

3.BASE



Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
Collector-Base Voltage 集电极基极电压	V_{CBO}	60	V
Collector-Emitter Voltage 集电极发射极电压	V_{CEO}	50	V
Emitter-Base Voltage 发射极基极电压	V_{EBO}	5	V
Collector Current 集电极电流	I_C	150	mA
Power dissipation 耗散功率	$P_C(T_a=25^{\circ}C)$	400	mW
Thermal Resistance Junction-Ambient 热阻	$R_{\theta JA}$	313	$^{\circ}C/W$
Junction and Storage Temperature 结温和储藏温度	T_J, T_{stg}	-55to+150 $^{\circ}C$	

■ Device Rank 产品分档







Rank 档位	O	Y	GR	BL
H_{FE} Range	70-140	120-240	200-400	350-700

■Electrical Characteristics 电特性


(TA=25℃ unless otherwise noted 如无特殊说明, 温度为 25℃)

Characteristic 特性参数	Symbol 符号	Min 最小值	Type 典型值	Max 最大值	Unit 单位
Collector-Base Breakdown Voltage 集电极基极击穿电压 (IC=100uA, IE=0)	BVCBO	60	—	—	V
Collector-Emitter Breakdown Voltage 集电极发射极击穿电压 (IC=1mA, IB=0)	BVCEO	50	—	—	V
Emitter-Base Breakdown Voltage 发射极基极击穿电压 (IE=100uA, IC=0)	BVEBO	5	—	—	V
Collector-Base Leakage Current 集电极基极漏电流 (VCB=60V, IE=0)	ICBO	—	—	100	nA
Emitter-Base Leakage Current 发射极基极漏电流 (VEB=5V, IC=0)	IEBO	—	—	100	nA
DC Current Gain 直流电流增益 (VCE=6V, IC=1mA)	HFE	70	—	700	
Collector-Emitter Saturation Voltage 集电极发射极饱和压降 (IC=100mA, IB=10mA)	VCE(sat)	—	—	0.3	V
Base-Emitter Saturation Voltage 基极发射极饱和压降 (IC=100mA, IB=10mA)	VBE(sat)	—	—	1	V
Transition Frequency 特征频率 (VCE=6V, IC=10mA)	fT	200	—	—	MHz
Noise Figure 噪声系数 (VCE=6V, IC=0.1mA, f=1KHz)	NF	—	—	10	dB
Output Capacitance 输出电容 (VCB=10V, IE=0, f=1MHz)	Cob	—	—	3	pF

■ Typical Characteristic Curve 典型特性曲线



■Dimension 外形封装尺寸



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	3.300	3.700	0.130	0.146
A1	1.100	1.400	0.043	0.055
b	0.380	0.550	0.015	0.022
c	0.360	0.510	0.014	0.020
D	4.300	4.700	0.169	0.185
D1	3.430		0.135	
E	4.300	4.700	0.169	0.185
e	1.270 TYP		0.050 TYP	
e1	2.440	2.640	0.096	0.104
L	14.100	14.500	0.555	0.571
Φ		1.600		0.063
h	0.000	0.380	0.000	0.015