

SOD-523 ESD 静电保护二极管

■ Features 特点

Un-directional 单向

ESD Protection 静电保护

■ Applications 应用


MP3 Players 播放器

Digital Cameras 数码相机

Notebooks & Handhelds 笔记本或手持机

Cellular handsets and accessories 蜂窝手机及配件

Personal Digital Assistants 个人数码助手



■ Device Marking 产品打标

■ Absolute Maximum Ratings 最大额定值


Characteristic 特性参数	Symbol 符号	Rat 额定值	Unit 单位
ESD (IEC61000-4-2 contact discharge) @25°C接触放电	V_{ESD}	± 8	KV
ESD (IEC61000-4-2 air discharge) @25°C空气放电	V_{ESD}	± 15	KV
Peak Pulse Power @25°C峰值脉冲功率	P_{PK}	200	W
Peak Pulse Current @25°C峰值脉冲电流	I_{PP}	2.5	A
Lead Temperature 管脚温度	T_L	260	°C
Lead Solder Time 管脚焊接时间	T_L	10	S
Operating Temperature 工作温度	T_{op}	-40~85	°C
Junction Temperature 结温	T_J	-55~125	°C
Storage Temperature 储存温度	T_{stg}	-55~150	°C

■ Electrical Characteristics 电特性


($T_A=25^{\circ}\text{C}$ unless otherwise noted 如无特殊说明, 温度为 25°C)

Characteristic Parameters 特性参数	Symbol 符号	Min 最小值	Typ 典型值	Max 最大值	Unit 单位	Condition 条件
Reverse Stand-off Voltage 反向工作电压	V_{RWM}			36	V	
Reverse Breakdown Voltage 反向击穿电压	V_{BR}	40			V	$I_{\text{T}}=1\text{mA}$
Reverse Leakage Current 反向漏电流	I_{R}			1	μA	$V_{\text{RWM}}=36\text{V}$
Clamping Voltage 钳位电压	V_{C}		50		V	$I_{\text{PP}}=1\text{A}, t_{\text{p}}=8/20\mu\text{s}$
Clamping Voltage 钳位电压	V_{C}		70		V	$I_{\text{PP}}=2.5\text{A}, t_{\text{p}}=8/20\mu\text{s}$
Diode Capacitance 二极管电容	C_{D}		10		pF	$V_{\text{R}}=0\text{V}, f=1\text{MHz}$


V_{RWM}	Reverse Working Voltage 反向工作电压
$V_{\text{R(BR)}}$	Reverse Breakdown Voltage 反向击穿电压@ $I_{\text{T}}=1\text{mA}$
I_{T}	Test Current 测试电流
I_{R}	Reverse Leakage Current 反向漏电流@ V_{RWM}
V_{C}	Clamping Voltage 钳位电压
I_{PP}	Reverse Peak Pulse Current 浪涌电流
C_{D}	Diode Capacitance 二极管电容 $V_{\text{IO}}=0\text{V}, V_{\text{P-P}}=30\text{mV}, f=1\text{MHz}$




■ Typical Characteristic Curve 典型特性曲线



■ Typical Application 典型应用



■ Dimension 外形封装尺寸



Unit mm	A	A1	b	c	D	E	E1	E2	L	θ
Max.	0.77	0.70	0.35	0.15	0.85	1.30	1.70	0.20	0.07	7°
Min.	0.51	0.50	0.25	0.08	0.75	1.10	1.50	REF.	0.01	REF.